

Technical Data Sheet

Product Name: JC LUB PE-09

Chemical Composition: Special Lubricant Wax

Function: JC LUB PE-09 is compatible with all synthetic & natural rubber, especially compatible with halogenated elastomers.

Sr. No.	Properties	Unit	Specifications
1	Appearance	-	White powder
2	Melting point	°C	95 - 110
3	Dry loss (105°C for 60 min.)	%	≤ 3
4	Flash point	°C	230-260
5	Ash Content	%	0.5

Advantage:

Excellent flow properties
 Gives smooth surface of all rubber products by the improvement in dispersion of fillers
 Internal lubricant benefits in filler corporation Acts as an external lubricant aids in easy removal of Moulded parts

Standard Packing: 25kg Bag

Shelf life: 2 year from D.O.M

Storage: Store in cool and dry place away from rain, snow, heat & direct sunlight

Dosage: As per requirement

Mode of Action: It acts as a processing aid in EPDM extrusion and Moulded rubber compounds which imparts excellent flow properties. It is useful in polymers like Natural and Synthetic Rubbers which avoid mould fouling in Reclaim rubber and Butyl compounds. It is advisable to add JC LUB PE-09 together with the filler.

Declaration: All Information in This Publication is in Accordance With Our Present Experience and Knowledge. However, Since We Have No Influence on the Way in Which Our Products Are Treated and Used, We Can Not take Any Responsibility in This Respect. The User Must Assume Responsibility Himself For Checking Whether The Products Are Suitable For The Purpose And Use Proposed By Him. All Existing Proprietary Rights, laws And Regulations Shall Be Observed.

Jayam Chemicals LLP

Plot no. 31/A, Part A, Opp. Baumer Industries,
 1st phase, GIDC Vapi-396195,
 GSTIN/UIN: 24AAGFJ3239G1ZK
 Phone: 0260- 2425399
 Email: info@jayamchemicals.com
<https://www.jayamchemicals.com/>